


www.micromatic.com

Part No.	Description	Shipping Weight	Box Dimensions
CDI842	8 Product Lines/2 Glycol Lines	.27 kg (per 305mm)	TBD
		.60 lbs (per foot)	TBD

Performance

Product Lines	1/4" I.D. x 3/8" O.D. Brewery Approved Brewmaster II Barrier Tubing			
Glycol Cooling Lines	3/8" I.D. x 1/2" O.D. Polyethylene Tubing			
	Outgoing: Blue Color Coded			
	Return: Red Color Coded			
Moisture Barrier Wrap	Food Quality Barrier Film			
Cold Transfer Wrap	Aluminum Foil			
Insulation	19mm (¾") Closed Cell			
Black Diamond [®] Jacket	15% more thermally efficient than tape. Braiding reinforced, resistant to tearing			
Exterior Marks	Sequential Foot Marking, Every 610mm (2 Feet)			
Fire Rating	Class 1 - Self extinguishing to BS3924, Class 1 when applied to insulation.			
Certification	NSF/ANSI Standard 51 Food Equipment Materials.			

Dimensions



	Toll Free: 1-(866) 327-4159				
	West	Central	Southeast	Northeast	
	19791 Bahama Street	10726 North Second Street	2364 Simon Court	4601 Saucon Creek Road	
www.micromatic.com	Northridge, CA 91324 Tel. (818) 701-9765	Machesney Park, IL 61115 Tel. (815) 968-7557	Brooksville, FL 34604 Tel. (352) 799-6331	Center Valley, PA 18034 Tel. (610) 625-4464	
	Fax. (818) 701-9844	Fax. (815) 968-0363	Fax. (352) 796-2429	Fax. (610) 625-4466	