Direct Draw Dispenser



Pro-Line 95" - 5 Keg

- Designed by beer-industry experts for performance and value.
- Integrated glass rinser: condition the glass with cold water before pouring.
- Rugged keg slides extends floor life.
- Full-size drain tray larger work area and improved hygiene.







Integrated cold water glass rinser.



Feature





Listed by Edison
Testing Laboratories.
Conforms to UL & NSF Standards.

Part No.	Exterior Finish	Doors	Shipping Weight	Box Dimensions
<u> MDD94</u>	Black With Solid Doors	3	195 kg	2438mm L x 762mm W x 1143mm H
			429 lbs	96 1/2"L x 30"W x 45"H
MDD94S	Stainless Steel With Solid Doors	3	195 kg	2438mm L x 762mm W x 1143mm H
			429 lbs	96 1/2"L x 30"W x 45"H

Operating Performance

Capacity of 1/2 Kegs	5	
Cubic Feet (liters)	39.2 (1112)	
Draft Towers	2	
Faucets	4	
Beer Tower Approval	NSF 7.0 & NSF 18	
Approval	ETL Listed	
Condenser HP	1/3	

Running Amps	6.7	
Voltage	115/60/1	
Plug Type	NEMA-5-15P	
Cord Length	8'	
Refrigerant	R-134a	
Charge oz (Grs)	12.30 (350)	

Exterior	All Models: 18 gauge stainless steel top, 22 gauge solid doors, 24 gauge steel front, sides and back. Black Models: Front, sides, back and doors black vinyl over steel. Stainless Steel Models: Front, sides, back & doors are stainless steel.	
Interior	20 gauge stainless steel floor, rugged false floor, reinforced frame, 24 gauge galvanized walls	
Ventilation	Front and back ventilated	
Plumbing	Automatic condensate evaporator, no drain connection required. Evaporator condensate has been plumbed to a condensate pan located in the compressor housing.	
Glass Rinser	15 – 20 PSI Water Connection	
Insulation	Foamed-in-place using high density, CFC-free polyurethane; 1-1/2" top, walls and floor.	
Accessories	Castors or 6" Fixed Legs	

Dimensions



