

Model # **LPA-1-50-1115**



Model# LPA-1-50-1115 :

Designed for single gas applications (Co₂, N₂ or "beer gas"). This alarm module is preset to notify the operator when the gas pressure reaches 40psi. Changing the cylinder will automatically reset the alarm.

AMBIENT OPERATING CONDITIONS:	0 to 150 Deg. F
SET POINT REPEATABILITY:	+/- 1% of adjustable range
ENCLOSURE MATERIAL:	ABS Plastic
PRESSURE CONNECTION:	3/8" Barb
PRESSURE ADJUSTMENT:	Factory set to 40 PSI *
MAX INLET PRESSURE:	300 PSI
MINIMUM INLET PRESSURE:	60 PSI
ELECTRICAL REQUIREMENTS:	120v / 15a
AUDIBLE ALARM:	80db @ 10cm
DIMENSIONAL INFORMATION:	7.75" x 4.75" x 2.25"

***Custom alarm set point available
*****Please Specify*******

**** The Beverage Gas Alarm can be configured to have custom alarm set points. This allows the gas alarm to be used with any beverage gas system application. Let us know the current system pressure, we can calibrate an alarm just for your system. The Beverage Gas Alarm can be built separate from the sensor module incase it is not appropriate to run gas lines to the alarm.**