

Model # **LPA-2-100-1115**



## Model# LPA-2-100-1115 :

Designed for dual gas applications (N2/Co2 gas blenders, Nitrogen generators/ bulk Co2). This alarm module is preset to notify the operator when the gas pressure reaches 85 psi. Changing the gas cylinder / restoring the gas supply will automatically reset the alarm.

<b>AMBIENT OPERATING CONDITIONS:</b>	0 to 150 Deg. F	
<b>SET POINT REPEATABILITY:</b>	+/- 1% of adjustable range	
<b>ENCLOSURE MATERIAL:</b>	ABS Plastic	
<b>PRESSURE CONNECTION:</b>	3/8" Barb	
<b>PRESSURE ADJUSTMENT:</b>	Factory set to 85 PSI *	*Custom alarm set point available
<b>MAX INLET PRESSURE:</b>	300 PSI	*****Please Specify*****
<b>MINIMUM INLET PRESSURE:</b>	110 PSI	
<b>ELECTRICAL REQUIREMENTS:</b>	120v / 15a	
<b>AUDIBLE ALARM:</b>	80db @ 10cm	
<b>DIMENSIONAL INFORMATION:</b>	9.75" x 5.75" x 2.25"	

**\*\* The Beverage Gas Alarm can be configured to have custom alarm set points. This allows the gas alarm to be used with any beverage gas system application. Let us know the current system pressure, we can calibrate an alarm just for your system. The Beverage Gas Alarm can be built separate from the sensor module incase it is not appropriate to run gas lines to the alarm.**